


Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (currently amended) A photothermographic material comprising, at least an image forming layer containing at least a photosensitive silver halide, a non-photosensitive organic silver salt, a reducing agent and a binder on at least one side of a support, wherein a content of silver iodide in the photosensitive silver halide is 5% by mole or more, the binder contains polymer latex in an amount of 60% by weight or more, and the reducing agent is a compound represented by the following general formula (R):

General formula (R)




wherein R¹¹ and R^{11'} each independently represent an alkyl group having 1 to 20 carbon atoms, R¹² and R^{12'} each independently represent a hydrogen atom or a group capable of substituting for a hydrogen on a benzene ring, L represents a -S- group or a -CHR¹³- group, R¹³ represents a hydrogen atom or an alkyl group having 1 to 20 carbon atoms, and X¹ and X^{1'} each independently represent a hydrogen atom or a group capable of substituting for a hydrogen on a benzene ring.

2. (original) The photothermographic material according to claim 1, wherein the polymer latex is a polymer having a glass transition temperature of -20°C to 60°C.

3. (original) The photothermographic material according to claim 1, wherein the polymer latex contains a styrene-butadiene copolymer.

4. (currently amended) The photothermographic material according to claim 1, wherein the binder contains polymer latex copolymerized using 10% by weight to 70% by weight of the monomer represented by the following ~~general~~ formula (M):

~~General~~ formula (M)



wherein R⁰¹ and R⁰² are each independently a hydrogen atom, an alkyl group having 1 to 6 carbon atoms, a halogen atom or a cyano group, provided that R⁰¹ and R⁰² are not both hydrogen atoms.

5. (currently amended) The photothermographic material according to claim 4, wherein, in ~~general~~ formula (M), R⁰¹ is a hydrogen atom and R⁰² is a methyl group.

6. (original) The photothermographic material according to claim 4, wherein the polymer latex is copolymerized using 1% by weight to 20% by weight of a monomer having an acidic group.

7. (original) The photothermographic material according to claim 4, wherein a

glass transition temperature of the polymer latex is -30°C to 70°C.

8. (original) The photothermographic material according to claim 4, wherein a glass transition temperature of the polymer latex is -10°C to 35°C.

9. (original) The photothermographic material according to claim 4, wherein the polymer latex contains a halogen ion in the latex solution in an amount of 500 ppm or less thereof.

10. (original) The photothermographic material according to claim 4, wherein the polymer latex is a styrene-isoprene copolymer latex.

11. (original) The photothermographic material according to claim 1, wherein R¹¹ and R^{11'} are each independently a secondary or a tertiary alkyl group having 3 to 15 carbon atoms, in the reducing agent represented by general formula (R).

12. (original) The photothermographic material according to claim 1, further comprising a development accelerator.

13. (currently amended) The photothermographic material according to claim 12, wherein the development accelerator contains a compound represented by the following general formula (A-1):


General formula (A-1)

$Q_1\text{-NHNH-}Q_2$

wherein Q_1 is an aromatic group bonding to $\text{-NHNH-}Q_2$ via a carbon atom, or is a heterocyclic group; and Q_2 is a carbamoyl group, an acyl group, an alkoxy carbonyl group, an aryloxy carbonyl group, a sulfonyl group, or a sulfamoyl group.

14.(currently amended) The photothermographic material according to claim 12, wherein the development accelerator contains a compound represented by the following general formula (A-2):

General formula (A-2)



wherein R_1 represents an alkyl group, an acyl group, an acylamino group, a sulfonamide group, an alkoxy carbonyl group, or a carbamoyl group; R_2 represents a hydrogen atom, a halogen atom, an alkyl group, an alkoxy group, an aryloxy group, an alkylthio group, an arylthio group, an acyloxy group, or a carbonic ester group; and R_3 and R_4 each independently represent a hydrogen atom or a group which can be substituted for a hydrogen on the benzene ring. R_3 and R_4 may join to each other to form a condensed ring.

15. (original) The photothermographic material according to claim 1, further comprising an organic polyhalogen compound as an antifoggant.

16. (currently amended) The photothermographic material according to claim 15, wherein the organic polyhalogen compound is represented by the following **general formula (H)**:

General formula (H)



wherein Q is an alkyl group, an aryl group, or a heterocyclic group; Y is a divalent linking group; n is 0 or 1; Z₁ and Z₂ are each a halogen atom; and X is a hydrogen atom or an electron attractive group.

17. (original) The photothermographic material according to claim 1, wherein the content of the silver iodide in the photosensitive silver halide is 40% by mole or more.

18. (original) The photothermographic material according to claim 1, wherein an average grain size of the photosensitive silver halide is 5 nm to 80 nm.

19. (original) The photothermographic material according to claim 1, wherein an average grain size of the photosensitive silver halide is 5 nm to 40 nm.

20. (original) The photothermographic material according to claim 1, wherein the photosensitive silver halide is formed in the absence of the non-photosensitive organic silver salt.

21. (original) The photothermographic material according to claim 1, further containing a compound that can be one-electron-oxidized to provide a one-electron oxidation product which releases one or more electrons.

22. (original) An image forming method using the photothermographic material according to claim 1, wherein the photothermographic material is exposed by scanning with a laser beam.

23. (original) The image forming method according to claim 22, wherein the laser is emitted from a laser diode.

24. (original) The image forming method according to claim 23, wherein the laser diode has a peak strength in a wavelength of 350 nm to 440 nm, and has an intensity of 1 mW/mm² to 50 W/mm².

25. (original) The image forming method according to claim 23, wherein the laser diode has a peak strength in a wavelength of 380 nm to 410 nm.

26. (new) The photothermographic material according to claim 1, wherein the silver iodide content of the photosensitive silver halide is 80% by mole or more.

27. (new) The photothermographic material according to claim 1, wherein the silver iodide content of the photosensitive silver halide is 90% by mole or more.

28. (new) The photothermographic material according to claim 14, wherein the R₃ and R₄ in the formula (A-2) join to each other to form a condensed ring.

29. (new) The photothermographic material according to claim 28, wherein the condensed ring is a naphthalene ring.

30. (new) The photothermographic material according to claim 14, wherein the R₁ is a carbamoyl group.